



CITAL

PIETRA



REALMONTE / FLAMED

FEATURES

ORIGIN Europe

STONE Calciclastic limestone

CHARACTERISTICS Light cream background, with subtle nuances of bronze-gray, and taupe tones. Small rocks and granules in dark browns, grays, rusty-orange and black color.

SIZE 3/8" (1cm), 1/2" (1.2cm), 3/4" (2cm), 1 1/4" (3cm)

RECOMMENDED USES Interior/exterior walls, interior/exterior floors, heavy traffic areas, fireplaces, columns, mouldings, etc.

POSSIBLE FINISHES Honed, Polished, Brushed, Sandblasted, Sandblasted+Brushed, Flamed, Flamed+Brushed, Bush Hammered.

Finishes are specific to each marble/stone type. Please inquire for finishes available.

Note: Sealer must be used after final installation for protection against oil and water based staining compounds.

TECHNICAL INFORMATION

Volumetric Weight	2567 Kg/m ³
Compression Breaking Load	953 kg/cm ²
Compression Breaking Load After Freezing Test	1030 kg/cm ²
Bending Strength	105 kg/cm ²
Thermal Linear Expansion Coefficient	5 m/m°C
Water Absorption	1.73 %
Apparent Porosity	4.44 %
Abrasion Test	4.2 mm
Impact Test	minimal fall height: 40 cm
Frost Resistance	48 Freeze and Thawing Cycles

CUSTOM SIZES MADE TO ORDER